

TECHNICAL SPECIFICATION

| | |
|---------------------|---------------------|
| Range in open area | ~80 m |
| Channels | 2 independent |
| Mic element | dynamic capsule |
| Characteristic | uni-directional |
| Impedance | 600Ω ± 30% |
| Frequency UHF range | ~518 – 690 MHz nom. |
| Frequency steps | 800 kHz nominal |
| ERP output | <10 mW |
| Batteries x2 | 2x AA (1,5 V) |
| Ta | 0 °C...+35 °C |
| Dimensions | ∅50/35 x 250 mm |
| Weight | 2 x 260 g |



| | |
|-----------------------|-------------------|
| Antenna | 2 x 190 mm/50 Ohm |
| Oscillation | PLL synthesized |
| Frequency stability | ±0,003 % |
| Receiver sensitivity | -50 dB ± 2 dB |
| Audio frequency range | 50 – 18.000 Hz |
| Audio dynamic | >105 dB |
| S/N ratio | 102 dB |
| THD | <0,5 % |
| Audio output | ~500 mV |
| Mixed output | ∅6,3 mm |
| Balanced output | XLR A+B |
| Ta | 0 °C...+35 °C |
| Dimensions | 210 x 50 x 180 mm |
| Weight | 700 g |



| | |
|--------------|---------------------|
| Voltage pri | 100-240 V~ 50/60 Hz |
| Voltage sec | 13,5 V== |
| Current sec | 0,6 A |
| Cable lenght | ≈1,1 m |
| Polarity | ⊖ ⊕ ⊕ |

