

TECHNICAL SPECIFICATION

Range in open area	~140 m
Channels	2 independent
Mic element	dynamic capsule
Characteristic	uni-directional
Impedance	600Ω ± 30%
Frequency UHF range	~518 – 690 MHz nom.
Frequency steps	250 kHz nominal
ERP output	<10 mW
Batteries x2	2 x AA (1,5 V)
Ta	0 °C...+35 °C
Dimensions	∅50/35 x 250 mm
Weight	2 x 320 g



Antenna BNC	2 x 260 mm/50 Ohm
Oscillation	PLL synthesized
Frequency stability	±0,003 %
Receiver sensitivity	-54 dB ± 2 dB
Audio frequency range	50 – 18.000 Hz
Audio dynamic	>120 dB
S/N ratio	105 dB
THD	<0,5 %
Audio output	~500 mV
Mixed output	∅6,3 mm
Balanced output	XLR A+B
Ta	0 °C...+35 °C
Dimensions	420 x 55 x 220 mm
Weight	1550 g



Voltage pri	100-240 V~ 50/60 Hz
Power On/StdBy	2,5 W/0,2 W
Voltage sec	12,0 V==
Current sec	1,0 A
Cable lenght	≈1,8 m
Polarity	⊖ ⊕

